

GENERAL

Design Basic functions In partnership with Gusto MSC Offshore Wind maintenance Oil & Gas maintenance

Accommodation

Classification ABS

 ♣A1 Self Elevating Unit, ♣AMS, ♣ACCU DNVGL

№1A1 Self Elevating Unit, №E0

DIMENSIONS

Length o.a. 57.00 m Length b.p.p. 56.00 m Beam mld. 32.00 Depth mld. 5.50 m Hull draught 3.50 m Leg length Variable load 76.0 m 800 t m² Cargo deck area 1000 Deck load 6 t/m²

TANK CAPACITIES

 m^3 Ballast water 450 m³ Fuel oil (service) 320 Potable water (service) 360 95 m^3 Sewage 125 m^3 Buffer tank Deck scupper drain tanks 150 m^3

PERFORMANCES (APPROX.)

Speed (at summer draught) Designed for survival High number of jacking cycles Frequent jacking

ELEVATED PERFORMANCE (ABS)

MILD SURVIVAL HARSH SURVIVAL 30 m Maximum water depth 55 m 6 10.5 Air gap m m Maximum wave height 7.5 13 m m Wind speed 32.5 35.0 m/s m/s Surface current 1.0 m/s 1.0 m/s

kn

JACKING SYSTEM

Туре Rack & Pinion Pre load 1,830 t/leg Jacking speed (hull) 0.8 m/mint PROPULSION SYSTEM

Main engines Propulsion power Azimuthing thrusters

AUXILIARY EQUIPMENT

Electric grid Main generator sets Emerg. generator set

DECK LAY-OUT

Anchor mooring winch Capstans Main crane

Auxiliary crane Fast rescue craft Life boats

ACCOMMODATION

Crew / industry personnel Facilities (Galley / Mess / etc)

NAUTICAL AND COMMUNICATION EQUIPMENT

Radar systems DP – system GMDSS

OPTIONS Helideck

Leg encircling crane

Extended Accommodation unit Circular leg configuration Propulsion installation Class approved DP-system

Gas sensing / alarm system Entertainment system

Suitable for Super Puma AS332L2

LEL, SO₂ according to MODU code IP TV, V-SAT

D-19.5m Stiff lattice boom 160 t at 15 m Jib length appr. 50m Suitable for up to 90 persons For lower water depths Various configurations ABS ♣DPS-2 DNV DPS(2)

Diesel - Electric, 690 V, 60Hz

4x 1,650mm FP in nozzles,

4x 1,000 ekW at 1,800 rpm

Stiff lattice boom 160 t at 15 m

400 ekW at 1,800 rpm

Jib length appr. 50m

12.5 t at 30 m

2x 90 pers

50 persons

90 person

2x fwd and 2x aft

4x Electric motors of 900kW each

690 V, 440 V and 230 V - 60 Hz



DG JACK 5632 P



DAMEN SHIPYARDS GORINCHEM

Member of the DAMEN SHIPYARDS GROUP

Industrieterrein Avelingen West 20 4202 MS Gorinchem

P.O. Box 1 4200 AA Gorinchem The Netherlands

phone fax +31 (0)183 63 99 11 +31 (0)183 63 21 89

info@damen.com www.damen.com